

T3

UNIQUE DESIGN

TESTED ACCORDING TO

- » EN ISO 13849
- » EN 60204-32
- » EN 62061
- » EN 62745
- » DNV



The special feature of the T3 transmitter is its versatility. The customer can configure it to suit his individual requirements and choose between toggle switches, pushbuttons and joysticks with digital or analogue functions. The T3 transmitter also offers LED indicators and an optional graphic display for the clear transmission of information.

TECHNICAL DATA

PROTECTION CLASS	IP 65
TEMPERATURE RANGE	-20 to +60 °C
WEIGHT	approx. 1400 g
DIMENSIONS	220 x 140 x 150 mm (W/D/H)
FREQUENCY RANGE	432-481/863-930 MHz; 2.4 GHz
BATTERY TECHNOLOGY	exchangeable, NiMH
OPERATING TIME	up to 20 hours
OPERATING RANGE	> 100 m

OPTIONS

- STOP Cat. 3 PLe / SIL3
- Safe digital control functions up to Cat. 3 PLe / SIL3
- Safe analogue control functions up to Cat. 3 PLe / SIL3
- LED feedback
- 2.1" graphic display
- Tilt sensor
- Presence sensor
- Vibration alarm
- Control panel lighting
- Cable control with optional charging function
- CAN cable control
- Multi-operation
- User-defined switch-off time
- Customised labelling
- Bottom housing available in red, blue or grey
- Shoulder hook
- Shoulder cross belt
- Belly belt
- Neck belt

